



Cabinet & Trim Enamel Interior Satin / Melamine Finish

- Door Won't Stick After 2 Hours of Dry Time*
- Excellent Flow & Levelling
- Dries to a Hard, Durable Finish
- Easy Clean Surface
- Resists Dirt, Grime & Household Chemicals
- Sandable
- Soap & Water Clean-Up
- Mildew-Resistant Paint Finish

No. 7520 White
No. 7523 Deep Base



2 Coats Required
for Optimal Protection



Spread Rate:
Up to 37 m² (400 sq. ft.)
Coverage



Dry Time:
1 Hr. Dry to Touch
2 Hr. Recoat



Clean-Up:
Soap & Water

WHITE: READY TO USE OR ADD TINTING COLOURANTS.

**DEEP BASE: DO NOT USE WITHOUT THE ADDITION OF TINTING COLOURANTS.
PROTECT FROM FREEZING**

WHERE TO USE

Recommended for interior wood, drywall, masonry, vinyl and other properly prepared and primed surfaces. Ideal for kitchen and bathroom cabinets and doors, windows, trim & moulding.

SURFACE PREPARATION[†] (Proper Surface Preparation is Required.)

- All surfaces must be clean, sound, dry and free of any dirt, oil and grease stains.
- Remove mildew stains with a mildew stain removing product.
- Remove all loose and peeling paint; scuff sand glossy surfaces; caulk and repair imperfections. [†]Sand all wood surfaces in the direction of the wood grain to the desired smoothness. Remove all dust from sanded surfaces with a damp, lint free cloth and allow to dry.

PRIME

- Priming is recommended on all surfaces. On previously painted surfaces and on new wood, masonry and vinyl surfaces, or on surfaces with heavy stains, prime with a product such as BEHR[®] Kitchen, Bath & Trim Primer & Sealer No. 75 prior to topcoating with this product. Follow all label instructions. For best results, sand primer coat prior to topcoating.

APPLICATION

- Apply when air temperature is between 10-32° C.
- Stir before and during application.
- When working with more than one can of the same product, intermix to ensure colour uniformity.
- Do not thin.
- Brush: Apply a thin coat using a high quality synthetic brush. For best results, apply paint with a high quality 100% Nylon brush.
- Roller: Use a high quality 6 mm nap roller cover.
- Airless Sprayer: .013" - .015" spray tip, 60 mesh filter.
- OPTIONAL: In between coats, sand lightly with 320-400 grit sand paper.
- Certain colours may require 2 or more coats to achieve complete hide.
- NOTE: If touch-up is necessary, same application method is recommended.

DRY TIME

- *Darker colours may require additional dry time. Longer dry time required in cooler temperatures and higher humidity.
- Cabinets, doors and windows can be closed as early as 2 hours after final topcoat.
- After 2 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.
- Do not use on floors.

DISPOSAL

- Properly dispose of all soiled rags.
- For disposal of empty containers and unused product, contact your household refuse collection service.
- To reduce waste, consult with your retailer or an online paint calculator to determine the correct amount of paint to purchase.

LIMITED WARRANTY

- Visit www.behr.com/warranty or call 1-800-661-1591 for more information.

[†]WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

***LIFETIME LIMITED WARRANTY** Behr Process Corporation warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified on the label during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. The clause of limitation of liability which follows is inapplicable in Quebec. **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute. To obtain warranty service, call 1-800-661-1591, or contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A 2L3. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

MAY IRRITATE EYES AND SKIN. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Wear eye protection and protective clothing. Use only with adequate ventilation. Keep out of reach of children. **FIRST AID TREATMENT:** Contains TITANIUM DIOXIDE, KAOLIN, AND NEPHELINE SYENITE. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.

