



## Alkyd Semi-Gloss Enamel

- Professional Quality Interior/Exterior Semi-Gloss Finish
- Performance of an Oil-based Paint with Easy Soap & Water Clean-up
- Outstanding Flow & Levelling
- Excellent Adhesion
- Less Odour than Oil-based Paint
- Durable Hard Finish
- Easy Stain Removal
- Mildew-Resistant Paint Finish

**NO. 3900 White**  
**NO. 3930 Deep Base**



**2 Coats Recommended**  
for Optimal Durability



**Spread Rate:**  
**Rough 33-37 m<sup>2</sup>**  
**Smooth 46-51 m<sup>2</sup>**



**Dry Time:**  
**2-4 Hr. Dry to Touch**  
**4-8 Hr. Recoat**



**Soap & Water**  
Clean-Up

**WHITE: READY TO USE OR ADD TINTING COLOURANTS.**

**DEEP BASE: DO NOT USE WITHOUT THE ADDITION OF TINTING COLOURANTS.**

**PROTECT FROM FREEZING.**

### WHERE TO USE

Properly prepared and primed wood, hardboard, metal, drywall, plaster, concrete, masonry and other sound above-grade interior/exterior surfaces. Ideal for Doors, Trim, Moulding, Cabinetry, Walls, Railings and Wrought Iron. **Do not use on horizontal surfaces subject to foot traffic.**

### PREPARATION† (Proper Surface Preparation is Required)

All surfaces must be clean, sound, dry and free of any dirt, oil and grease stains. Remove mildew stains with a mildew stain removing product. Interior Wood Trim, Door & Cabinetry: Remove all loose and peeling paint; scuff sand glossy surfaces; caulk and repair imperfections. Sand all wood surfaces in the direction of the wood grain to the desired smoothness. Remove all dust from sanded surfaces with a damp, lint-free cloth. Exterior Wood: Use a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner. Thoroughly rinse the treated surfaces with clean water and allow to dry before any paint application. Interior/Exterior Concrete & Masonry: Allow new stucco, plaster and masonry to cure for 30 days. Use a concrete & masonry degreaser & cleaner to clean and prepare the surface. Powerwash to remove chalk on exterior surfaces. Interior/Exterior Metal: Etch galvanized metal. Follow all label instructions.

### PRIME

On Interior/Exterior surfaces with heavy stains, new wood, metal, concrete and masonry surfaces, use a product such as BEHR® Multi-Surface Interior/Exterior Stain-Blocking Primer & Sealer No. 436 prior to topcoating with this product.

### \*LIFETIME LIMITED WARRANTY

Behr Process Corporation warrants to you, the original residential consumer purchaser, the performance of this product as described on this label for so long as you reside in your home. THIS WARRANTY IS NOT VALID WHEN THE PRODUCT IS NOT PROPERLY APPLIED TO A PROPERLY PREPARED SURFACE OR CARED FOR IN ACCORDANCE WITH THE LABEL DIRECTIONS. This warranty is not transferable. If this product is found not to perform as specified on the label during the warranty period, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. The clause of limitation of liability which follows is inapplicable in Quebec. **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute. To obtain warranty service, call 1-800-661-1591, or contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A 2L3. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-661-1591.

### APPLICATION

DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure colour uniformity. Use adequate ventilation during application and drying process. Certain colours may require 2 or more coats to achieve complete hide and coverage. Use product when air and surface temperatures are 10-32°C. Apply a thin coat using a high quality synthetic brush, 6-10 mm nap roller or an airless sprayer (.013"-.017" spray tip, 60 mesh filter). NOTE: If touch-up is necessary, same application method is recommended.

### DRY TIME

Darker colours may require additional dry time. Longer dry time required in cooler temperatures and higher humidity. Wait at least 7 days before rinsing or cleaning the surface with a mild, non-abrasive detergent

### DISPOSAL

Properly dispose of all soiled rags. For disposal of empty containers and unused product, contact your household refuse collection service.

†**WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**MAY IRRITATE EYES AND SKIN.** Avoid contact with eyes, skin and clothing. Do not breathe fumes. Wear eye protection and protective clothing. Use only with adequate ventilation. Keep out of reach of children. **FIRST AID TREATMENT:** Contains TITANIUM DIOXIDE; NEPHELINE SYENITE; POLYETHYLENE GLYCOL MONO-C12-14-ALKYL ETHER SULFATE SODIUM SALT; AND STYRENE/ACRYLIC COPOLYMERS. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.



©2021 Behr Process Corporation  
Canadian Office • Calgary, Alberta • [behr.com](http://behr.com)  
V.O.C. <50 g/L • REV. 06/21